



Harmonite® 100 Product Data Sheet

Description

Harmonite 100 is an organic-encapsulated, inorganic composite powder currently available for applications requiring smaller particles and a tighter particle distribution than standard Harmonite. Like other Harmonite powders, the organic phase is rich in polar resins and asphaltenes. The inorganic phase includes a blend of materials including calcium carbonate, aluminum oxide, Kaolin clay, glass fibers, titanium dioxide and other inert ingredients. Harmonite 100 is asbestos free.

Applications

Harmonite 100 is a versatile, multi-functional product that can be used as an economical base compound for building new product formulations or as a specialty additive. It is ideally suited for use in rubber compounding for its plasticizing and other effects that can help reduce power consumption and reduce incorporation time while simultaneously eliminating or reducing consumption of multiple more expensive ingredients. It is also well suited for use in industrial coatings, mastics, adhesives, and sealants.

Chemical Compatibility

Harmonite 100 is compatible with a wide variety of commonly used formulation ingredients including: synthetic rubber compounds like butyl and SBR, as well as SBS & SIS block copolymers, C5/C9 and other resins, various petroleum pitch/bitumen, asphalts, naphthenic distillates and petroleum solvents.

Typical Composition		
Organics	29% +/- 3%	Asphaltenes (~42%) Resins (~21%) Aromatics (~22%) Saturates (~15%)
Inorganics	Balance	Calcium Carbonate Aluminum Oxide Titanium Dioxide Kaolin Clay Glass fiber Moisture Other inert ingredients

Note – Other inert ingredients include silica



Harmonite® 100 Product Data Sheet

Typical Product Characteristics		
Product Form	Finely divided, coarse grained powder	
Color	Black	
Odor	None	
Specific Gravity	1.9	
Bulk Density (average)	38 lbs/ft ³	
Softening Point	Approx 280 - 295°F (extracted organic)	
Flow Characteristics	Flows readily with minimal agitation upon removal from bags or super sacks – exhibits moderate compressibility with little to no cohesive properties during storage and transit. Live bottom active feed systems recommended for bulk storage.	
Particle Size Distribution (Mass basis)	Sieve Stack Analysis	Cumulative Mass % < Indicated Size
	<150 μm (<100 mesh)	99%
	<90 μm (<170 mesh)	64%
	<75 μm (<200 mesh)	28%
	<45 μm (<325 mesh)	4%
Shelf Life	12 months	
Moisture content	<1%	
Solubility	Organic phase soluble in solvents like mineral spirits, aromatics like xylene, etc. and longer straight chain hydrocarbons. Insoluble in water and common alcohols.	
Reactivity	Polar resins/asphaltenes have been known to exhibit polymeric behavior via hydrogen bonding and van der Waals interactions.	
Typical Applications	Gaskets, hose covers, floor mats, conveyor covers, industrial coatings, mastics, adhesives, sealants, etc.	

Conditions of Sale and Limitations of Warranties

All Harmonite materials and products of Recycled Shingle Solutions, LLC (RSS) are sold subject to the Recycled Shingle Solutions, LLC Terms and Conditions of Sale, and all other terms and conditions set forth in any technical or product data sheets, invoices, order acknowledgments, and/or bills of lading. All technical information, recommendations, and other statements with respect to such materials and products set forth in this data sheet or otherwise are based on information believed by to be reliable by RSS, but RSS neither guarantees nor warrants the accuracy or completeness thereof. It shall be the sole responsibility of the user to determine the suitability of such materials or product for each intended use, and the user assumes all risks and liability in connection with or resulting from the use or inability to use such materials or products. To the exclusion of all other remedies, RSS warrants and agrees to replace, or at its sole option, to refund the purchase price with respect to, that portion of any material or product returned to RSS within thirty (30) days of the receipt by user of such materials or products and that is deemed by RSS to be defective in material or workmanship after inspection by RSS. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE, AND SHALL BE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, ARISING BY LAW OR CUSTOM, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY EXPRESSLY DISCLAIMED. IN NO EVENT SHALL RSS BE LIABLE FOR ANY INDIRECT, INCIDENTAL, SPECIAL, OR CONSEQUENTIAL OR OTHER DAMAGES OF ANY KIND WHATSOEVER (INCLUDING ATTORNEYS' FEES) ARISING WITH RESPECT TO THE MATERIALS OR PRODUCTS, INCLUDING, BUT NOT LIMITED TO, LOSSES OR DAMAGES ARISING OUT OF CLAIMS FOR LOSS OF BUSINESS, GOODWILL, PROFITS, OR ARISING OUT OF THIRD PARTY ACTIONS, AND EACH USER HEREBY WAIVES FOR ITSELF AND ITS SUCCESSORS AND ASSIGNS ANY SUCH CLAIMS AGAINST RSS.

Contact:
Pearce Daley
Sales Director for RSS, LLC.
813.977.0202 (o)
813.323.1620 (m)

RSS, LLC.
6075A Lees Mill Road
Forest Park, GA 30297
www.rssharmonte.com
© October 2017 RSS